



# PALATAC

Acrylic polymer emulsion pressure sensitive adhesives (PSAs) used in label stock, tape and specialist adhesive markets.



	Water proofing	Paper labels	Construction tape	Double-sided tape	Speciality tape	Protective	Graphic films	Flooring	Thermal paper	Minimum application temperature (°C)	Solids (%)	pH	Viscosity (mPas)	Peel adhesion (PET/Steel) 180° (N/25 mm)	Static Shear (h)	Tack (N/25 mm2)	
Removable adhesive tape	Typical applications								Typical properties*							Special features	
<b>PALATAC R2930</b>		●				●				-5	54	7.5	500	4	-	5	No primer needed, food grade
<b>PALATAC R2909S**</b>		●					●	●		-5	50	4.5	500	4	> 8	3	No primer needed, clean removal
<b>PALATAC R2915**</b>		●				●		●		-5	55	8.0	500	4	4	5	High initial tack, clean removal
<b>PALATAC R2913ST</b>		●				●				-5	53	4.5	900	4	4	4	Ready to use, clean removal
Permanent adhesive tape																	
<b>PALATAC P4908**</b>				●	●					-20	54	5.0	600	> 14	> 200	> 12	High cohesion and repositionable
<b>PALATAC P4909**</b>		●		●	●					-20	54	5.5	400	> 12	> 200	> 12	Permanent adhesive for label applications
<b>PALATAC P4901M**</b>			●	●	●	●				-20	54	5.5	300	> 18	> 100	> 15	High peel and high shear for direct coating
<b>PALATAC P4910A</b>			●	●	●					-20	52	6.5	500	> 15	>100	> 14	Good adhesion to LSE substrates
<b>PALATAC FL3802</b>	●					●				-20	51	6.0	600	8	> 150	6	High shear, repositionable, film lamination
<b>PALATAC P4918</b>				●		●				-5	54	5.5	300	n/a	n/a	n/a	Primer for overlamine and construction
<b>PALATAC P4922</b>			●	●	●					-20	53	6.5	450	> 18	> 40	> 15	Adheres to metallic foils and LSE substrates
<b>PALATAC PW2245**</b>				●	●					-20	54	5.0	600	> 14	> 200	> 12	Fast wash off in alkaline solution
<b>PALATAC P5120D</b>	●	●								-20	54	7.5	500	> 15	5	> 15	Formulated for freezer use
<b>PALATAC P4945</b>			●	●	●		●			-20	54	5.5	600	> 14	> 100	> 15	High tack, high adhesion to LSE substrates
<b>PALATAC P4932LV</b>			●	●			●			-20	58	5.5	1500	> 18	> 20	> 15	Flooring and carpet tile adhesive
<b>PALATAC P5100F</b>	●	●				●				-20	52	6.0	400	> 10	-	> 10	Water resistance for drum labels

\*Not product specification

\*\*Specification can be altered based on customer requirement



**PALEUS**  
ACRYLICS



**PALEUS Group**

Pitman Road, Denaby Main,  
Doncaster, DN12 4LJ, UK

**E:** [service@paleus.com](mailto:service@paleus.com)

**T:** +44 (0) 1709 861373



[www.paleusacrylics.com](http://www.paleusacrylics.com)